



Anybus 邊緣網關 M-Bus WLAN

借助 Anybus 邊緣網關，可以輕鬆安全地訪問來自工業設備和機器的數據，還允許在應用程序生命週期內進行完整的數據和設備管理。Edge 網關支持邊緣智能、智能分散操作，可以在靠近數據源的地方執行。從網關，用戶定義的數據通過 HMS Hub 通過安全連接提供到雲。該解決方案非常適合監控應用，還可以通過物聯網應用以智能方式控制所有連接的工業設備。



特點與優勢

- HMS 中心連接
- 實現輕鬆的遠程控制和管理
- 提供Modbus-TCP客戶端/服務器和Modbus-RTU主/從接口
- 啟用 OPC UA、MQTT、SNMP、SNTP 通信
- Powerful graphical edge intelligence design tool
- Simple web configuration interface
- Firewall, OpenVPN & password protection
- NAT routing
- TLS data encryption
- HTTPS port usage
- Device initiated connections
- Central or local device management
- Mass deployable updates
- Real-time status information
- Alerts and automatic responses

連通性

MODBUS-RTU

- 4096 個值 (最多 8192 個值，包括數組成員)
- Modbus-RTU 主/從
- 多達 128 個設備

MODBUS TCP

- 4096 個值 (最多 8192 個值，包括數組成員)
- Modbus-TCP 客戶端/服務器

OPC UA 規範

- 支持發現服務
- 用戶名和密碼認證
- 安全策略 Basic256Sha256 / Basic128Rsa15 / None

MQTT 規範

- MQTT 客戶端充當發布者/訂閱者
- MQTT 版本 3.1 - 3.1.1
- 支持 Last Will 和 QoS 0-2
- 用戶名和密碼認證
- TLS

SNMP 管理器

- 多達 128 個代理和 4096 個值陷阱接收器

網絡連接

- OpenVPN 客戶端：將設備集成到虛擬專用網絡中
- DHCP 服務器：最多 100 個客戶端 · 最多 20 個靜態租用
- NAT：在本地（內部）和全球（外部）網絡之間路由流量 · 最多 1000 個映射 · 最多 50 個靜態映射
- 防火牆：過濾傳入流量 · 最多 1000 條規則（包括傳出流量的動態規則） · 最多 50 條靜態規則

無線局域網/WIFI

- IEEE 802.11 a/b/g/n
- 雙頻段（2.4 GHz、5 GHz）

移動總線

- M-Bus Master 接口符合 EN 13757-2
- 300 - 9600 比特/秒
- 多達 64 個設備

SECURITY



Secure data at every level

Protecting the data on the journey between the factory floor and the enterprise software is only part of the story. Device and data security is an ever-growing concern in our day to day business. True security must be present at every level in an end to end solution. It would be no benefit to encrypt the data transfer if the value in the payload is already compromised. Data must be handled with care from the point it enters a system until the point it leaves.



Security features of Anybus Edge

- Firewall, OpenVPN & password protection – Controlling access to the devices is paramount in security. Access is not just about stopping connections but also ignoring them completely – to not be brought down by denial of service attacks.
- Root access authentication – Controlling the root access to a system ensures certain routines can never be interfered with.
- TLS data encryption – Protecting privacy and data integrity with strong encryption means that data gets to where it needs to be without being manipulated.
- Standard port usage – The device pushes and pulls data utilizing the outbound HTTPS connection enabling easy integration with standard firewalled environments.



Manage your devices to be ready for the threats of tomorrow

There exists an ever changing landscape today in the world of security. With our new-found access to global libraries of features and software, we must be prepared to maintain the integrity of a system by keeping it up to date and protected from threats. The largest security threat to any system is an out of date device with a known vulnerability. The concept of a fully hardened device that will be able to survive in the field without updates and feature enhancements is already a debunked myth. By providing all levels of update capability, the Edge system is designed to keep you protected into the unknowns of the future.

ECOSYSTEM



CONFIGURATION



Sequence

The Anybus Edge Gateways are built for ease of use. They feature HMS Sequence, a powerful graphical programming tool, to build your desired on-device Edge Intelligence. Configuration and deployment can be done locally or remotely via a simple web interface.

For detailed information about programming please visit the configuration section on the product support page.

TECHNICAL SPECIFICATIONS

GENERAL

Software	
Operating System	IPC@CHIP RTOS-LNX Real-time operating system
HMS Sequence editor and runtime	Visual programming editor running on the internal web server - I/O mapping editor - Up to 8192 I/O values - Up to 1024 portal variables

Technical Details		Standard
Dimensions (L•W•H)	100 series: 79 x 46 x 107 mm 140 series: 79 x 65 x 107 mm	
Protection class	IP20, NEMA rating 1	IEC 60529
Enclosure material	Continuously hot-dip aluminium-zinc coated steel	
Installation position	Vertical position	
Mounting	DIN rail (35•7,5/15)	EN 50022

Certifications		Standard
UL	File number: Pending	UL 508 Ind. Cont. Eq.
CE	2014/30/EU (EMC)	IEC 61000-6-3

		IEC 61000-6-2 IEC 62368-1
--	--	------------------------------

Electrical Characteristics	
Power	24 VDC, BL 3.50/03 connector +- 15 %
Current consumption	< 0.4 A

Hardware Characteristics	
Reverse voltage protection	Yes
Short circuit protection	Yes

Environmental Characteristics	
Operating temp	0 to +55 °C (+32 to +131 °F)
Storage temp	-20 °C to +60 °C
Relative Humidity	5 % to 85 % relative humidity, non-condensing

Immunity and Emission for Industrial Environment		Standard
Electrostatic discharge	+/-4 kV contact, +/-8 kV air	EN 61000-4-2
Electromagnetic RF fields	10 V/m 80 MHz - 1 GHz 3 V/m 1,4 GHz - 2,0 GHz 1 V/m 2,0 GHz - 2,7 GHz	EN 61000-4-3
Fast Transients	+/-2 kV DC, +/- 1 kV signal	EN 61000-4-4
Surge protection	+/- 0.5 kV CM / +/-1 kV DM on DC, +/-1 kV signal	EN 61000-4-5
RF conducted interference	10 V/rms	EN 61000-4-6
Emission (at 3 m)	0.15 MHz – 0.5 Mhz 40-30 dBµA/m (QP) 30-20 dBµA/m (Avg) 0.5 MHz – 30 Mhz 30 dBµA/m (QP) 20 dBµA/m (Avg)	EN 55016-2-3

Single Pack Accessories	
	Installation sheet

SECURITY

Encryption	TLS 2.3
------------	---------

WLAN/WIFI

Standards	IEEE 802.11 a/b/g/n Dual band (2.4 GHz, 5 GHz)
Modes	Wi-Fi client
Security	WPA/WPA2-PSK

Antenna interface	SMA female
-------------------	------------

M-BUS

Connectors	BL 3.50/10 connector
Speed	300 - 9600 bit/s
I/O data	4096 values
Number of slaves	Up to 64 devices

交貨內容

- 網關
- 快速入門文檔
- 連接器端子
- 不包括電源

訂購信息

訂購代碼	ABE04040
------	----------

包含快速入門文檔、USB 配置電纜。配置軟件可供下載。不包括
電源。3年保證。有關購買說明以及條款和條件，請參閱：[→ 如何購買→](#)

Copyright © 2020 HMS Industrial Networks - All rights reserved.